

TF RANGE



The TF model auger is applicable to Skid Loaders and Wheel Loaders with SAE J2513 universal front attachment. It has a compact and robust structure that encloses a transmission with planetary reduction gear. The wide range of tools and accessories available makes it versatile in the most diverse sectors such as construction, green maintenance, agriculture etc.



STANDARD TECHNICAL FEATURES

- Compact and robust body that contains all the components inside.
- Front and rear opening to easily reach the internal components for better maintenance
- Front and rear protective casings
- Planetary gearmotor for high performance even at low hydraulic flow rates
- Hexagonal drive shaft for quick tool change
- Hydraulic pipes L = 2000

| AUGER          |       | TF1     | TF2     | TF3     | TF4     |
|----------------|-------|---------|---------|---------|---------|
| Oil flow       | l/min | 18 / 50 | 20 / 60 | 40 / 90 | 60/125  |
| Max pressure   | bar   | 225     | 205     | 240     | 300     |
| Max torque     | Nm    | 1300    | 2600    | 4700    | 10500   |
| Speed          | rpm/l | 1,9     | 1,1     | 0,8     | 0,75    |
| A              | mm    | 275     | 325     | 375     | 380     |
| B              | mm    | 490     | 575     | 770     | 1060    |
| C (Hexagon)    | mm    | 50      | 50      | 50      | 70      |
| Weight         | kg    | 108     | 128     | 223     | 395     |
| Ø Drilling max | mm    | 400     | 600     | 800     | 1000    |
| Price          | £     | 2393,00 | 2689,00 | 3322,00 | 4608,00 |

Augers - TF range



OPTIONAL

|   |                                                                 |        |
|---|-----------------------------------------------------------------|--------|
| 1 | REVERSING VALVE                                                 | £      |
|   | FLOW REVERSING VALVE FOR OPERATING MACHINES WITH ONE-WAY SYSTEM | 579,00 |
| 2 | «FACCIA PIANA» QUICK COUPLERS**                                 | £      |
|   | Connection size 3/8"                                            | 60,00  |
|   | Connection size 1/2"                                            | 82,00  |
|   | Connection size 3/4"                                            | 192,00 |
|   | Connection size 1"                                              | 292,00 |

\*\* On request we can supply quick couplings different from those indicated  
All data are to be understood WITHOUT MACHINE ATTACHMENT  
FOR MACHINES WITH HIGH FLOW PRESSURE REDUCERS ON HYDRAULIC LINES ARE RECOMMENDED



BITS



STANDARD BITS ET

Suitable for medium mixture soils  
Blades and Lower Bits are interchangeable.

| Standard bits with hexagonal fitting CH50 | £       |
|-------------------------------------------|---------|
| ET Ø 100 length 1000 mm                   | 636,00  |
| ET Ø 120 length 1000 mm                   | 650,00  |
| ET Ø 150 length 1000 mm                   | 675,00  |
| ET Ø 200 length 1000 mm                   | 708,00  |
| ET Ø 250 length 1000 mm                   | 743,00  |
| ET Ø 300 length 1000 mm                   | 783,00  |
| ET Ø 350 length 1000 mm                   | 840,00  |
| ET Ø 400 length 1000 mm                   | 872,00  |
| ET Ø 450 length 1000 mm                   | 930,00  |
| ET Ø 500 length 1000 mm                   | 1008,00 |
| ET Ø 600 length 1000 mm                   | 1157,00 |
| Hexagonal fitting CH70                    | +15%    |



MEDIUM BITS ED

Suitable for drilling mid-high consistency soils with the presence of crushed stones  
Blades and Lower Bits are interchangeable.

| Hard Soils bits with hexagonal fitting CH50 | £       |
|---------------------------------------------|---------|
| ED Ø 150 length 1000 mm                     | 758,00  |
| ED Ø 200 length 1000 mm                     | 811,00  |
| ED Ø 250 length 1000 mm                     | 854,00  |
| ED Ø 300 length 1000 mm                     | 922,00  |
| ED Ø 350 length 1000 mm                     | 986,00  |
| ED Ø 400 length 1000 mm                     | 1115,00 |
| ED Ø 450 length 1000 mm                     | 1179,00 |
| ED Ø 500 length 1000 mm                     | 1315,00 |
| ED Ø 600 length 1000 mm                     | 1422,00 |
| Hexagonal fitting CH70                      | +15%    |



BITS



ROCK BITS ER

Suitable for drilling rock soils and road surfaces, lower bits and peaks made of widia material all interchangeable

| Rock BITS with hexagonal fitting CH50 | £       |
|---------------------------------------|---------|
| ER Ø 150 length 1000 mm               | 992,00  |
| ER Ø 200 length 1000 mm               | 1008,00 |
| ER Ø 250 length 1000 mm               | 1102,00 |
| ER Ø 300 length 1000 mm               | 1189,00 |
| ER Ø 350 length 1000 mm               | 1333,00 |
| ER Ø 400 length 1000 mm               | 1455,00 |
| ER Ø 450 length 1000 mm               | 1506,00 |
| ER Ø 500 length 1000 mm               | 1558,00 |
| ER Ø 600 length 1000 mm               | 2343,00 |
| Hexagonal fitting CH70                | +15%    |



COMPACTING BITS EC

Bits with a special profile which do not remove the soil but compact it at the sides.  
Useful for making holes to plant fence posts.

| Compacting BITS with hexagonal fitting CH50 | £      |
|---------------------------------------------|--------|
| EC Ø 50 length 1000 mm                      | 440,00 |
| EC Ø 60 length 1000 mm                      | 458,00 |
| EC Ø 70 length 1000 mm                      | 543,00 |
| EC Ø 80 length 1000 mm                      | 558,00 |
| EC Ø 90 length 1000 mm                      | 568,00 |
| EC Ø 100 length 1000 mm                     | 572,00 |
| EC Ø 110 length 1000 mm                     | 579,00 |
| EC Ø 120 length 1000 mm                     | 596,00 |
| EC Ø 130 length 1000 mm                     | 643,00 |
| EC Ø 140 length 1000 mm                     | 688,00 |
| EC Ø 150 length 1000 mm                     | 723,00 |
| Hexagonal fitting CH70                      | +15%   |

